

Texdecor - Casamance 2, rue d'Hem **59780 WILLEMS** France

Your notice of 22-06-2023

Your reference

Date 08-08-2023

Analysis Report 23.03469.02

Required tests :

BS 5867-2 (2008)

Sample id	Information given by the client	Date of receipt
T2314809	4019	22-06-2023

Reelle

Gina Créelle Order responsible

This report may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel. The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples. In assessing compliance with the specifications, we did not take into account the uncertainty on the test results.





CENTEXBEL • textile competence centre • www.centexbel.be • www.vkc.be

GENT • Technologiepark 70 • BE-9052 Zwijnaarde, Belgium • phone +32 9 220 41 51 • fax +32 9 220 49 55 • gent@centexbel.be GRÂCE-HOLLOGNE • Rue du Travail 5 • BE-4460 Grâce-Hollogne, Belgium • phone +32 4 296 82 00 • g-h@centexbel.be KORTRIJK • Etienne Sabbelaan 49 • BE-8500 Kortrijk, Belgium • phone +32 56 29 27 00 • fax +32 56 29 27 01 • info@vkc.be VAT BE 0459.218.289 • IBAN BE44 2100 4729 6545 • BIC GEBABEBB

0



Reference: T2314809 - 4019

Determination of the flammability of textile fabrics for curtains and drapes

Date of ending the test Standard used Product standard	07-08-2023 EN ISO 15025 (2002) BS 5867-2 (2008)				
Deviation from the standard	-				
Conditioning Testing atmosphere	20°C, relative humidity 65% 22°C, relative humidity 54%				
Information given by the client	Front = back				
The test specimens have not been	cleaned nor submitted to an ac				

The test specimens have not been cleaned nor submitted to an accelerated ageing procedure.

Flame application time (s) 15

	Length			Width		
	1	2	3	1	2	3
Flame or hole on edge		no	no	no	no	no
Flaming debris droplets		no	no	no	no	no

Type B performance requirements

No part of any hole nor any part of the lowest boundery of any flame shall reach the top edge or either vertical edge.

There shall be no separation of any flaming debris droplets

Conclusion

Flammability, of the uncleaned fabric, complies with the requirements of BS 5867-2:2008, type "B"

0